CertainTeed® Ridge Vent

12" Filtered Shingle-Over Ridge Vent



Designed with Internal Weather Filter and External Baffles

CertainTeed® Ridge Vent Filtered proves that outstanding beauty and performance can be combined.

Less than an inch in height, this molded, high-impact copolymer shingle-over ridge vent permits capping of the ridge with shingles like the rest of the roof.

CertainTeed Ridge Vents combined with sufficient intake vents, such as CertainTeed Intake Vent, are the most efficient and effective systems you can install.



CertainTeed® Ridge Vent

CertainTeed® Ridge Vent Filtered installs on the peak of the roof, allowing exhaust ventilation all along the roofline.



Imprinted slot guides for proper slot width

Highest quality co-polymer remains sturdy, nailable and flexible in all climates

Reinforced ribs for greater stability and rigidity

Built-in ventilating end plug seals the end

Cap shingles install easily making the vent virtually invisible

Nail holes located at 16" and 24" centers

Nail bosses, reinforced nail holes designated to prevent over nailing

Weather filter provides advanced protection from rain, snow, dust and insect intrusion

High gloss nailing lines for accurate, fast cap shingle nailing

Air slots have 18" sq. free vent area per linear ft.

External wind baffle creates low air pressure and helps pull air out of the attic

Features

- · Designed with an external baffle to deflect wind and weather over the vent to help protect the attic from rain and snow infiltration. The external baffle creates low pressure over the vent openings to "pull" air from the attic
- Internal weather filter provides a more complete barrier to help protect the attic from wind-driven rain, snow, dust and insects
- Easy installation has pre-printed slot guides for truss or ridge pole construction. Pre-drilled nail holes are designed to assure proper nailing
- 18" sq. of net free area per linear foot
- CertainTeed Ridge Vent is pre-formed to a 4/12 pitch, and fits pitches from 3/12 to 16/12
- Limited Lifetime Warranty and 5-Year SureStart™ Protection
- Ten 4' pieces per box / Weight: 18lbs. / Part #95983 Model #SHFVBL / Color: Black

Benefits

- · Works year-round to ventilate the attic
- Provides evenly distributed ventilation along the entire underside of the roof
- Slim design for visual appeal
- Provides a higher volume of airflow per square foot of attic area than any other fixed-vent system
- · Design maximizes airflow across the entire underside of roof sheathing
- · Changes in wind direction have no significant effect on vent performance
- Wind driven rain resistant to 110 MPH

ShingleVent II is Manufactured for CertainTeed







Corporation by Air Vent, Inc., Orrick, MO.



CertainTeed Corporation P.O. Box 860 Valley Forge, PA 19482

Professional: 800-233-8990 Consumer: 800-782-8777

www.certainteed.com http://blog.certainteed.com

GYPSUM • CEILINGS • INSULATION • PIPE

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS

© 10/13 CertainTeed Corporation, Printed in the U.S.A. Code No. 20-20-3460

